

Greenline GL62 High-Performance Carpet Adhesive

Special Note: Indoor use only

Installation

Use: Commercial

Use for:

- Commercial carpets: (polypropylene & Action Bac). latex unitary, urethane foam, unitary (Action Bac), urethane laminate, jute, hotmelt, woven, latex foam-backed and non-backed needle punched.
- Carpet to cushion (double glue-down) Approved Carpet Cushions
- Cushion to substrate (permanent)

Description

Type: Latex base

Color: Smooth, off-white paste

Taggants: Saturn Yellow and Fire Orange

Trowel: 1/8" x 1/16" x 1/8" V Notch - Rough Back Carpet
3/32" x 3/32" x 3/32" V Notch - Smooth Back Carpet

Open Time: None over porous substrates
10-15 minutes over non-porous substrates. Do not allow to skin over.

Working Time: 60 minutes
NOTE: Working times vary based on job conditions, substrates, temperature and humidity

Spread Rate: 1/8" x 1/16" x 1/8" V Notch 90-108 sq. ft. {10-12 sq. yd} per gallon - rough back carpet
3/32" x 3/32" x 3/32" V Notch 144-162 sq. ft. {16-18 sq. yd.} per gallon - smooth back carpet

Removal: Remove wet adhesive residue with a clean, white cloth dampened with warm soapy water.

- Use mineral spirits on a clean, white cloth for dried adhesive residue carefully following warnings on container.
- Do not wet wash carpet for 5 days after installation.

Advantages: 97% lower in emissions than current Carpet and Rug Institute (CRI) criteria

- Extremely versatile - for all carpet backings except vinyl
- Wet suction - holds down difficult to install carpet backings
- No open time required - over most substrates
- Long working time - great for large carpet installations
- Superior Bond Integrity - for heavy traffic areas
- Excellent Rebond -when re-rolling after installation
- Excellent trowelability - easy to use, easy to trowel
- Moisture and alkali resistant - allows installation on all grade levels of concrete
- No discernible odor

Shelf Life: Six (6) months (from date of manufacture) if not opened.
Keep from freezing and avoid high temperatures.

Available Units: 4 Gallon

VOC: VOC content: 0 g/L; calculated & reported, SCAQMD 1168

WARNING:	<p>This product contains no reportable hazardous ingredients.</p> <p>Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes. Wash skin thoroughly with soap and water. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed.</p> <p>KEEP OUT OF REACH OF CHILDREN. This product contains no reportable hazardous ingredients.</p> <p>Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes. Wash skin thoroughly with soap and water. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed.</p> <p>KEEP OUT OF REACH OF CHILDREN.</p>
-----------------	--

CAUTION:	<p>NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with federal, state and local waste disposal regulations. Do not flush adhesive down drains.</p> <p>Recommended storage temperature is below 90 degrees F.</p>
-----------------	--

DANGER:	<p>Do not sand, dry sweep, dry scrape, drill, saw, beadblast or mechanically chip or pulverize existing resilient flooring, backing, lining felt, or asphalt "cutback" adhesives or other adhesives. These products may contain asbestos fibers and/or crystalline silica.</p> <p>Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard.</p> <p>Smoking by individuals exposed to asbestos fibers greatly increases the risk of serious bodily harm. See current edition of the Resilient Floor Covering Institute's publication: "Recommended Work Practices for Removal of Resilient Floor Coverings" for instructions on removing all resilient floor covering structures.</p>
----------------	---

Read label and MSDS carefully before use.

HENRY Commitment

HENRY is committed to helping you get the best results in professionally installed floors. 60 years of experience combined with our relationships with the leading resilient, wood and carpet manufacturers ensure that you receive the products and the support you need to complete the job successfully and profitably.

SUBSTRATES: Concrete, underlayments, wood substrates, terrazzo and existing resilient on all grade levels as recommended by the carpet manufacturer.

INSTALLATION TIPS:

- Refer to carpet manufacturer's specific recommendations.
- Condition the area to be installed, adhesive and flooring at 65° F (18° C) or above for 48 hours before, during and 48 hours after installation.
- Floor must be sound, smooth, dry, clean and free of excessive moisture or alkali. Remove dirt, wax, loose paint and all other foreign matter that would interfere with a good bond such as curing agents and sealers.
- Stir any liquid that has settled on the surface into the adhesive.
- Full spread adhesive using recommended trowel. **NOTE:** Recommended trowel sizes are minimum requirements. Porous concrete and some carpet backings may require deeper notches. 100%

transfer of adhesive into the carpet backing must be obtained.

- Install carpet immediately into wet adhesive unless carpet or substrate is non porous. In this case, wait 10-15 minutes before installing carpet
- Within 60 minutes, cut, fit and reposition as recommended by the carpet manufacturer.
- Roll floor in both directions with a 75-100 lb. roller and seal seams as recommended by the carpet manufacturer. Stiff carpets should be rolled again after 2 hours. Restrict heavy traffic over carpet for 24 hours.
- As is customary with normal installation procedures, do not sand, dry seep, dry scrape, drill, saw, beadblast, or mechanically hip or pulverize existing resilient flooring, backing lining felt or asphalt "cutback" adhesives or other adhesives. These products may contain asbestos fibers and/or crystalline silica. Avoid creating dust. During the installation process, adequate ventilation of the work area should be maintained. Persons who are sensitive to odors and/or chemicals should avoid the work area. Inhalation of such dust is a cancer and respiratory tract hazard. Smoking by individuals exposed to asbestos fibers greatly increases the risk of serious bodily harm. See current edition of the Resilient Floor Covering Institutes publication "Recommended Work Practices for Removal of Resilient Floor Coverings" for instructions on removing all resilient floor covering structures.

WARRANTY: For complete warranty details, contact your dealer or our Customer Service Center.

- WW Henry Company warrants that GL62 will not break down or lose its cohesive strength due to a manufacturing or formulation defect for 10 years from the date of installation, subject to certain exclusions and limitations set forth in the warranty, if used for its stated purpose and applied in accordance to these instructions.

HENRY Commitment

HENRY is committed to helping you get the best results in professionally installed floors. 60 years of experience combined with our relationships with the leading resilient, wood and carpet manufacturers ensure that you receive the products and the support you need to complete the job successfully and profitably.

WEIGHT PER GALLON: 9.52 lb.

SHIPPING UNIT: Pail

QUANTITY PER PALLET: 48 Pails

UPC INFORMATION: 0 42369 21529 9

Recommended Architectural Specifications: "The adhesive as herein specified shall be HENRY GREENLINE GL62 High-Performance Carpet Adhesive as manufactured by WW Henry Company, of Aliquippa, Pennsylvania."

Products